



GE Reaves Engineering, Inc.
P.O. Box 791793
San Antonio, TX. 78279-1793
(210) 490-4506 Fax 490-4812

Framing Design Order Form

CLIENT NAME	PROPERTY ADDRESS		DATE
	CITY & STATE		COUNTY
FORM COMPLETED BY	PHONE (OFFICE)	PHONE (MOBILE)	GRE PROJECT No.

Building Description: ___ One Story ___ Two Story ___ Split Level ___ Other _____

Roof Finish Material: ___ Tile ___ Shingle ___ Metal ___ Other _____

Will electronic CAD files be provided for this project? ___ Yes ___ No
(If electronic CAD files are not provided, additional fees may be incurred)

Roof Framing: (Please select one option below and provide the requested information)
Note: If no selection is made, 2x8 rafters and 2x6 ceiling joists will be used at 24" o.c. by default.

<input type="checkbox"/>	Rafters & Ceiling Joists:	Preferred Rafter Size:	___ 2x6 ___ 2x8 ___ 2x10 ___ 2x12 ___ Other _____
		Preferred Rafter Spc'g:	___ 16" o.c. ___ 19.2" o.c. ___ 24" o.c. ___ Other _____
		Preferred Clg. Jst. Size:	___ 2x6 ___ 2x8 ___ 2x10 ___ Other _____
		Preferred Clg. Jst. Spc'g:	___ 16" o.c. ___ 19.2" o.c. ___ 24" o.c. ___ Other _____

<input type="checkbox"/>	Premanufactured Roof Trusses:	Preferred Truss Spc'g:	___ 16" o.c. ___ 19.2" o.c. ___ 24" o.c. ___ Other _____
		Truss Fabricator:	_____

<input type="checkbox"/>	SIP Panels:	Preferred Roof Panel Thickness:	_____ inches
		Panel Manufacturer:	_____

<input type="checkbox"/>	Other:	Please Describe:	_____

Floor Framing: (Please select one option below and provide the requested information)
Note: If no selection is made, 16" deep premanufactured floor trusses will be used at 24" o.c. by default.

<input type="checkbox"/>	Dimensional Lumber:	Preferred Joist Size:	___ 2x6 ___ 2x8 ___ 2x10 ___ 2x12 ___ Other _____
		Preferred Joist Spc'g:	___ 16" o.c. ___ 19.2" o.c. ___ 24" o.c. ___ Other _____

<input type="checkbox"/>	Premanufactured Floor Trusses:	Preferred Truss Depth:	___ 12" ___ 14" ___ 16" ___ 18" ___ 20" ___ 24"
		Preferred Truss Spc'g:	___ 16" o.c. ___ 19.2" o.c. ___ 24" o.c. ___ Other _____
		Truss Fabricator:	_____

<input type="checkbox"/>	Premanufactured I-Joists:	Preferred Joist Depth:	___ 9 1/2" ___ 11 7/8" ___ 14" ___ 16" ___ 18"
		Preferred Joist Spc'g:	___ 16" o.c. ___ 19.2" o.c. ___ 24" o.c. ___ Other _____
		Joist Supplier:	_____

<input type="checkbox"/>	SIP Panels:	Preferred Floor Panel Thickness:	_____ inches
		Panel Manufacturer:	_____

<input type="checkbox"/>	Other:	Please Describe:	_____

(Continued on next page)

PROPERTY ADDRESS

CITY & STATE

COUNTY

Wall Framing: (Please select one option below and provide the requested information)

Note: If no selection is made, conventional wood framed walls will be used at 16" o.c. by default.

Conventional Wood Framing: Preferred Stud Spacing: ___ 16" o.c. ___ 24" o.c. ___ Other _____

Wall Sheathing: ___ OSB @ Full Exterior - Thickness: _____ "

___ OSB Only As Required for Wall Bracing - Thickness: _____ "

___ Other - Please Describe: _____

SIP Panels: Preferred Wall Panel Thickness: _____ inches

Panel Manufacturer: _____

ICF Concrete Walls: Concrete Core Thickness: _____ inches

ICF Manufacturer: _____

Other: Please Describe: _____

Wall Bracing: Is wall bracing design requested for this project? ___ Yes ___ No

Engineered Wall Solutions: Do any exterior walls on this project exceed 12' in height? ___ Yes ___ No

Number of individual walls exceeding 12' - _____ (Engineered wall solutions are required for these walls if project is under City of San Antonio)

Signature	Date	
------------------	-------------	--